



EN ISO 20344:2011

POLAR
ADVENTURE
88039-00L

S3 HRO HI WR SRC

Size: 38-48
Weight: 780 gr.

Fit: 11

Working Environment:
 Multipurpose, Farming and Gardening, Farming and Gardening, Oil industry

FEATURES

UPPER
 No ladder H.T. Fabric
 MicroFiber TOP 1,8-2,0 mm
 Reflex insert

LINING
 3D Air circulation 320 gr.

ANTISLIP LINING
 DUALMICRO

INSOLE
 Climaction-Fit 337

TOE CAP
 Fiber cap SXT

RESISTANCE TO PERFORATION
 Textile resistant to 3.0 mm nail

TYPE
 Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO-SRC
 Sole resistant to 300°C by contact.
 With scaff cap and compound designed with VIBRAM for stability and grip performance. Outsole designed to strike the ground better and to improve self-cleaning. With anti-wear scaff cap.



SRC (SRA+SRB)

		SOLE 88 PU - RUBBER	
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.34	
	HEEL (CONTACT ANGLE 1°) ≥ 0.28	0.31	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19	
	HEEL (CONTACT ANGLE 1°) ≥ 0.13	0.15	

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole **337**
climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements
RESISTANT TO 3.0 mm. NAILS **fibercap sxt**

Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability
dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability
STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features
WED
 Wire Electricity Discharge
 Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other
HDry
 +WATERPROOF UPPER
 The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

